



PHILIPPINE CHILDREN'S MEDICAL CENTER
Quezon Avenue, Quezon City
ALTERNATIVE MODE

REQUEST FOR QUOTATION
No. RFQ- 2024-234

Date: _____
Name of Supplier: _____
Address: _____
Telephone No. _____

Please quote your lowest price as per specifications per item listed below thru Alternative Mode of Procurement - Negotiated Procurement **on or before May 13, 2024.**

Please **fax your quotation at 588-9997** or email at **danilonrodriguez@gmail.com/ pcmeproc@gmail.com / Attention:** _____

ITEM NO.	QTY	UNIT	DESCRIPTION	ABC/UNIT	TOTAL ABC	BRAND/ PACKAGING	MANUFACTURER	UNIT COST	TOTAL COST
1	280	kit	Continuous Glucose Monitoring (CGM) Sensors	3,080.00	862,400.00				
			<p>CGM Reader Specifications</p> <p>Blood glucose assay range: 20 to 500 mg/dL</p> <p>Blood ketone assay range: 0.0 to 8.0 mmol/L</p> <p>Reader size: 95 mm x 60 mm x 16 mm</p> <p>Reader weight: 65 grams</p> <p>Reader power source: One lithium-ion rechargeable battery</p> <p>Reader battery life: 7 days of typical use</p> <p>Reader memory: 90 days of typical use</p> <p>Reader operating temperature: 10 °C to 45 °C</p> <p>Reader storage temperature: -20 °C to 60 °C</p> <p>Operating and storage relative humidity: 10-90%, non-condensing</p> <p>Reader moisture protection: Keep dry</p> <p>Operating and storage altitude: -381 meters (-1,250 ft) to 3,048 meters (10,000 ft)</p> <p>Reader display timeout: 60 seconds (120 seconds when test strip is inserted)</p> <p>Radio Frequency: 13.56 MHz RFID; ASK Modulation; 124 dBuV/m</p> <p>Data Port: Micro USB</p> <p>Minimum Computer Requirements: System must only be used with EN60950-1 rated computers</p> <p>Mean service life: 3 years of typical use</p> <p>Power Adapter: Operating temperature: 10 °C to 40 °C</p> <p>USB Cable: Length: 94 cm (37 inches)</p> <p>CGM Sensor Specifications</p> <p>Sensor glucose assay range: Amperometric electrochemical sensor</p> <p>Sensor glucose reading range: 40 to 500 mg/dL</p> <p>Sensor size: 5 mm height and 35 mm diameter</p> <p>Sensor weight: 5 grams</p>						


		Sensor power source: One silver oxide battery Sensor life: Up to 14 days Sensor memory: 8 hours (glucose readings stored every 15 minutes) Operating temperature: 10 °C to 45 °C Sensor Applicator and Sensor Pack storage temperature: 4 °C to 25 °C Operating and storage relative humidity: 10-90%, non-condensing Sensor water resistance and ingress protection: IP27: Can withstand immersion into one meter (3 ft) of water for up to 30 minutes. Protected against insertion of objects > 12 mm diameter. Operating and storage altitude: -381 meters (-1,250 ft) to 3,048 meters (10,000 ft)					
				<u>862,400.00</u>			
PCMC Requirement:					<i>Please indicate below your delivery period in number of days.</i>		
Delivery Period:							
Warranty:							

Terms and Conditions:

Supplies to be delivered should have at least one (1) year and longer expiry
 Staggered Delivery and Staggered Payment for CY-2024

Documentary Requirements:

- Nego. Proc (53.9) - Small Value
- PhilGEPS Ref#:
- Mayor's/ Business Permit
- PhilGEPS Reg. No


 5-9-2024

 Signature over Printed Name
 Name of Supplier _____

For Certificate of Creditable Tax Withheld at Source (BIR Form N. 2307) and Certificate of Final Tax Withheld at Source (BIR Form No. 2306) please submit your latest/updated **BIR Certificate of Registration (BIR Form N. 2303) together with your quote.*